

TurningPoint ResponseCard RF LCD



Specification:

Size & Weight:

Height: 3.3 inches (83.3 mm)
Width: 2.1 inches (53.3 mm)
Depth: 0.3 inches (7.6 mm)
Weight: 1.0 ounce (28.4 grams)*

*Weight is with two coin cell CR2032 (3.0 v) lithium batteries

Range:

Range: 200 ft range (400 ft coverage)

Battery & Power:

Battery: Two coin cell CR2032 (3.0 v) lithium batteries
Sleep mode: Deep sleep mode when not in use
Battery life: Average battery life 6 - 12 months

Input Device Capability:

12 keys (1/A - 10/J, Ch/Channel, ?)

Answer key - Answers automatically transmitted

Programmable - Manually enter new ID number

ResponseCard Programmer compatible

User Identification:

Select a channel in under 5 seconds, indicating session choice

Select a channel anytime - even when a session is underway

Channel selection is stored in non-volatile memory

Channel selection is preserved until changed by participant

Display:

LCD viewable screen display: H x W (0.4 inches 1.1 mm x 0.6 inches 1.5 mm)

Indicators: Response confirmation, Channel setting, Battery life

LED Light:

Green light: Response confirmation (3 seconds)

Red light: Response unconfirmed

RF Technology:

82 channels can be running at once within close proximity

Fully FFC, CE and Industry Canada certified

Will not interfere with other technologies